

M A T E R I A L   S A F E T Y   D A T A   S H E E T

VIGON INTERNATIONAL INC.  
AIRPORT ROAD  
EAST STROUDSBURG, PA 18301

| HMIS HAZARD  
| CLASSIFICATION  
|  
| HEALTH = 2  
| FLAMMABILITY = 2  
REACTIVITY = 0

FOR CHEMICAL EMERGENCY DURING TRANSPORTATION ONLY

INFOTRAC 1-800-535-5053

24 HRS PER DAY, 7 DAYS PER WEEK

I. PRODUCT IDENTIFICATION

-----  
ITEM#: B-00475

PRODUCT NAME: BENZALDEHYDE NATURAL

CAS #: 100-52-7

FORMULA: C H O

7 6

II. COMPOSITION OR INFORMATION ON INGREDIENTS

-----  
Product and/or component(s) carcinogenic at 0.1% or greater according to OSHA, IARC, NTP, or Other: NO

III. HAZARD IDENTIFICATION

-----  
POTENTIAL HEALTH EFFECTS...

PRIMARY ROUTES OF EXPOSURE: Eyes, Skin

EFFECTS OF EXPOSURE: May be irritating to the skin and eyes.

Prolonged contact, as with clothing wetted with material, may cause more severe irritation and discomfort. Vapors or mist, in excess of permissible concentration, or in unusually high concentration generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the throat and nose, headache, nausea and drowsiness.

#### IV. EMERGENCY AND FIRST AID PROCEDURES

---

**INHALATION EXPOSURE:** If headache, irritation, nausea, or drowsiness occurs, remove to fresh air and call a physician.

**EYE CONTACT:** Remove contact lenses. Flush eyes with cool water for at least 15 minutes. Hold eyelids apart while flushing to rinse entire surface of eyes and lids. Call a physician.

**SKIN CONTACT:** Remove contaminated clothing. Wash skin with mild soap and water. If irritation or any other symptoms occur, call a physician.

**INGESTION:** If patient is conscious and can swallow, administer water and call a physician or poison control center immediately. Do not induce vomiting.

**OTHER INSTRUCTIONS:** None.

#### V. FIREFIGHTING MEASURES

---

**FLASH POINT (CC, F):** 150

**RECOMMENDED FIRE EXTINGUISHING MEDIA:** Carbon-dioxide, foam, or dry chemicals.

**RECOMMENDED PROTECTIVE EQUIPMENT FOR FIREFIGHTERS AND SPECIAL PROCEDURES:** Use of self-contained breathing apparatus with full face piece operated in the positive pressure demand mode when fighting fires. Protective clothing is recommended. Prevent contact with skin and eyes. Cool fire exposed containers.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Combustible liquid. Avoid heat, sparks, and open flames.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide, carbon monoxide, fumes.

**HAZARDOUS POLYMERIZATIONS:** None occurs.

#### VI. ACCIDENTAL RELEASE MEASURES

---

**PROCEDURES IN CASE OF ACCIDENTAL RELEASE, BREAKAGE, OR LEAKAGE:** Ventilate area. Avoid breathing vapor. Avoid contact with skin, eyes and clothing. Pressure demand air supplied respirators should always be worn when the airborne concentration of the contaminant or oxygen is unknown. Otherwise, wear NIOSH approved respiratory protection and other personal protective equipment as appropriate for the potential exposure hazard. Remove any sources of flame or sparks. Contain spill if possible. Absorb spill with vermiculite or other suitable absorbant material. Shovel up material and place in approved disposal

container. Dispose of in accordance with current local, state, and federal laws and regulations.

#### VII. HANDLING AND STORAGE INFORMATION

---

**PRECAUTIONS TO BE TAKEN IN HANDLING:** Avoid breathing vapors. Avoid contact with skin, eyes and clothing. Avoid prolonged or repeated exposure. Wash thoroughly after handling.

**STORAGE:** Keep tightly closed. Store in cool dry place.

#### **WARNING!**

**FULL STRENGTH MATERIAL MAY BE IRRITATING TO THE SKIN AND EYES.**

**VAPOR IS IRRITATING TO THE THROAT AND LUNGS.**

**BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE ANESTHETIC EFFECTS.**

#### VIII. EXPOSURE CONTROLS AND PROTECTION INFORMATION

---

**THRESHOLD LIMIT VALUE (TLV):** Not established.

**OSHA PERMISSIBLE EXPOSURE LIMIT (PEL):** Not established.

**RESPIRATORY PROTECTION:** Vapor respirator.

**VENTILATION:** Mechanical (General) - meeting ACGIH standards.

**PROTECTIVE GLOVES:** Rubber gloves.

**EYE PROTECTION:** Safety glasses.

**OTHER PROTECTIVE EQUIPMENT:** Safety shower, eye wash.

#### IX. PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE:** Colorless to slightly yellow liquid.

**ODOR DESCRIPTION:** Characteristic strong, cherry like odor.

**BOILING POINT:** 178°C

**VAPOR PRESSURE (mm Hg @ 20° C):** 1 @ 26°C

**VAPOR DENSITY (AIR = 1):** 3.7

**SPECIFIC GRAVITY @ 25 C (WATER = 1):** 1.04

**SOLUBILITY IN WATER:** Insoluble

#### X. STABILITY AND REACTIVITY

---

**CONDITIONS/MATERIALS TO AVOID:** Normally stable under proper conditions. Avoid excessive heat, open flames, or other sources of ignition. Avoid contact with strong acids, alkalies, and/or oxidizing agents.

XI. TOXICOLOGICAL INFORMATION

-----  
LD50 ORAL (RAT): 1300 mg/kg  
LD50 ORAL (MOUSE): 28 mg/kg  
LD50 INTRAPERITONEAL (MOUSE): 9 mg/kg  
LD50 SUBCUTANEOUS (RABBIT): 5000 mg/kg  
LD50 ORAL (GUINEA PIG): 1000 mg/kg

XII. ECOLOGICAL INFORMATION

-----  
Not found

XIII. DISPOSAL CONSIDERATION

-----  
WASTE DISPOSAL METHOD: Under RCRA, it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

XIV. TRANSPORTATION INFORMATION

-----  
TRANSPORTATION BY GROUND, AIR OR VESSEL....  
PROPER SHIPPING NAME: BENZALDEHYDE  
HAZARD CLASS: 9  
IDENTIFICATION NUMBER: UN1990  
PACKING GROUP: III  
PRIMARY LABEL REQUIRED: CLASS 9  
PRIMARY PLACARD REQUIRED: CLASS 9  
SEGREGATION: Usual precautions for combustible liquids.

XV. REGULATORY INFORMATION

-----  
This substance contains no materials subject to the reporting requirements of SARA TITLE III SECTION 313.

XVI. OTHER INFORMATION

-----  
Containers should be either reconditioned by CERTIFIED firms or properly disposed of by APPROVED firms. Disposal of containers should be in accordance with applicable laws and regulations. "Empty" drums should not be given to individuals. Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive material. Cutting or welding of empty

containers may cause fire, explosion, or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep containers closed and drum bungs in place.

**\*\*\* DISCLAIMER \*\*\***

-----  
THE INFORMATION IN THIS MSDS WAS OBTAINED FROM CURRENT AND REPUTABLE SOURCES. THIS DATA IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR USE OF THIS PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR, EXPENSE RESULTING FROM IMPROPER USE OF THIS PRODUCT.

LAST REVISED: 01/12/10

DATE PRINTED: 11/11/11